

# RAM Drilling Products Group

## Air Dryers Desiccant

100 to 3,600 PSIG - 100 SCFM to 3,000 SCFM capacity



### RAM Air Dryers

Like all the RAM air treatment products, our products are rugged, tough and dependable and intended for use in Drilling Applications

- Rig Air
- Bulk Air
- High Pressure Air
- Accessories: Air Filters and Automatic Drain Valves for all dryers

The following Dryers are Rated at:

- 100 Degrees "F"
- 125 PSIG

Allow for a 15 % purge air loss when designing air systems with a desiccant air dryer

Model:	DAD450	DAD590	DAD750	DAD1100	DAD1550	DAD2100	DAD3000
Flow @ SCFM	400	500	750	1000	1500	1750	2000
Voltage: 110-240	YES	YES	YES	YES	YES	YES	YES
Electrical Panel NEMA 4	YES	YES	YES	YES	YES	YES	YES
Connections-	2.0" NPT	2.0" NPT	2.0" NPT	3.0" FLG	4.0" FLG	4.0" FLG	4.0" FLG
Dimensions "IN"	73x58x42	104x55x51	107x57x51	115x66x59	117x74x59	119x82x59	125x86x67
Weight Lbs.	1350	1475	2150	2875	4170	4425	9000

For model for Bulk Air at 40 to 65 PSIG or High Pressure at 2,000 to 3,600 PSIG Applications and for air flow capacities not listed here.

Please consult with RAM Sales

